



NRSA Series

SMD Power Inductors For Automotive

Size 6045




FEATURES

- U
- =
- O k
- \ #
- ° -# j
- j


APPLICATION

- #

Dimensions: [mm]

















Land Pattern: [mm]





Electrical Properties:

	(μ H)	(A)	(A)	(A)	(A)	(m)
VkO°	k V					
VkO°	k V					
VkO°	k U					
VkO°	k U					
VkO°	k U					
VkO°	k U					
VkO°	k U					
VkO°	k U					
VkO°	k U					
VkO°	k U					
VkO°	k U					
VkO°	k U					
VkO°	k U					
VkO°	k U					
VkO°	k U					
VkO°	k U					
VkO°	k U					
VkO°	k U					
VkO°	k U					
VkO°	k U					







Soldering Reflow:

Preheat condition: 150 ~200 / 60~120 sec.


Allowed time above 217 : 60~90 sec.

Max temperature: 260 .

Allowed Reflow time: 2x max.


Packaging Information:

Tape Dimension :




A0 (mm)	B0 (mm)	D (mm)	P0 (mm)	P1 (mm)	W (mm)	K0 (mm)	E (mm)	T (mm)
6.4±0.1	6.4±0.1	1.5±0.1	4.0±0.1	12.0±0.1	16.0±0.3	4.7±0.1	1.75±0.1	0.40±0.05

Peel force of top cover tape:




The peel force of top cover tape shall be between 0.3 to 1.17 N

Reel Dimension : [mm]



Packaging Quantity:



1000 Pcs/Reel

2 Reel /Inner box(2K Pcs)

3 Inner box/Carton box(6K Pcs)

Cautions and Warnings:

Storage Conditions :

- The storage period is within 12 months after the completion of production. Be sure to follow the storage conditions (temperature: -5 to 35°C, humidity: 75% RH Max).If the storage period elapses, the soldering of the
-
-
-

Operation Instructions:

-
-
-
-